


JW-HD144N

N-type Bifacial Mono Module

455-475W

IEC61215(2021), IEC61730(2016)
 ISO9001:2015: Quality Management System
 ISO14001:2015: Environmental Management System
 ISO45001:2018: Occupational health and safety management systems



475W

Maximum Power Output

21.82%

Maximum Module Efficiency

0~+5W

Power Output Tolerance



10-30% Additional Power Generation

30 years lifespan brings 10-30% additional power generation comparing with conventional P-type module



Better Weak Illumination Response

Higher power output even under low-light environments like on cloudy or foggy days



ZERO LID (Light Induced Degradation)

N-type solar cell has no LID naturally which can increase power generation



Better Temperature Coefficient

Higher power generation under working conditions, thanks to passivating contact cell technology



Lower LCOE

Higher bifaciality, higher power output and lower BOS cost




Wider Applicability

More application scenes like BIPV, vertical installation, snowfield, high-humid, windy and dusty area

Jolywood Delivers Reliable Performance Over Time

- Leader of N-type bifacial manufacturer
- Full-automatic facility and industry-leading technology
- Best-in-class durability and reliability
- BNEF Tier One

Linear Performance Warranty



12 Years Product Material & Workmanship

30 Years Linear Performance Warranty

JW-HD144N Series | N-type Bifacial Mono Module

Electrical Properties | STC*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	455	460	465	470	475
MPP Voltage (Vmp) (V)	41.8	42.0	42.2	42.4	42.6
MPP Current (Imp) (A)	10.89	10.96	11.02	11.09	11.16
Open Circuit Voltage (Voc) (V)	50.2	50.4	50.6	50.8	51.0
Short Circuit Current (Isc) (A)	11.50	11.56	11.62	11.69	11.76
Module Efficiency (%)	20.90	21.13	21.36	21.59	21.82

*STC: Irradiance 1000 W/m², Cell Temperature 25°C, AM1.5
The data above is for reference only and the actual data is in accordance with the practical testing
Power Measurement Tolerance ±3%

Electrical Properties | NOCT*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (Pmax) (W)	345	349	352	356	360
MPP Voltage (Vmp) (V)	39.3	39.5	39.7	39.8	40.0
MPP Current (Imp) (A)	8.78	8.84	8.88	8.94	9.00
Open Circuit Voltage (Voc) (V)	48.0	48.2	48.4	48.6	48.8
Short Circuit Current (Isc) (A)	9.27	9.32	9.37	9.43	9.49

*NOCT: Irradiance 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s

Operating Properties

Operating Temperature (°C)	-40°C~+85°C
Maximum System Voltage (V)	1500V DC (IEC)
Maximum Series Fuse Rating (A)	25
Power Tolerance	0~+5W
Bifaciality*	80%
Front Static Load	Snow load 5400Pa, Wind load 2400Pa

*Bifaciality=Pmaxrear (STC) /Pmaxfront (STC) , Bifaciality tolerance:±5%

Temperature Coefficient

Temperature Coefficient of Pmax*	-0.300%/°C
Temperature Coefficient of Voc	-0.250%/°C
Temperature Coefficient of Isc	+0.045%/°C
Nominal Operating Cell Temperature (NOCT)	42±2°C

*Temperature Coefficient of Pmax±0.03%/°C

Mechanical Properties


Cell Size	166.00mm*83.00mm
Number of Cells	144pcs(12*12)
Module Dimension	2095mm*1039mm*30mm
Weight	28kg
Front / Rear Glass*	2.0mm/2.0mm
Frame	Anodized Aluminium Alloy
Junction Box	IP68 (3 diodes)
Length of Cable	4.0mm ² , +300mm/-180mm (Cable length can be customized)

*Heat strengthened glass




With Different Power Generation Gain (regarding 460W as an example)

Power Gain (%)	Peak Power (Pmax) (W)	MPP Voltage (Vmp) (V)	MPP Current (Imp) (A)	Open Circuit Voltage (Voc) (V)	Short Circuit Current (Isc) (A)
10	497	42.0	11.83	50.4	12.46
15	515	42.0	12.26	50.4	12.91
20	534	42.0	12.69	50.4	13.36
25	552	42.1	13.12	50.5	13.81
30	570	42.1	13.56	50.5	14.27

Engineering Drawing (unit: mm)



Characteristic Curves | HD144N-460



Packaging Configuration

Packing Type	20'GP	40'GP	40'HQ
Piece/Pallet		36	
Pallet/Container	5	11	22
Piece/Container	180	396	792

*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jolywood (Taizhou) Solar Technology Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

