

Three-phase On-grid String Inverter

SPI3K~6K-B Series



High Yield

- 2 independent MPPT, more generation
- Advanced control algorithms and high adaptation ability to the grid, improving the stability of power generation system



Safe and reliable

- IP65 for outdoor application
- Integrated DC&AC SPD



Easy O&M

- Intelligent WiseSolar Plus APP+ cloud platform provides all-round visual O&M
- Support Remote online upgrade, convenient and efficient



Household friendly

- Small size, easy to install and use
- Natural cooling, ensuring low environmental noise



Technical Specification

Items	SPI3K-B	SPI4K-B	SPI5K-B	SPI6K-B
DC Input (PV)				
Max. PV power (recommend)	3.9kWp	5.2kWp	6.5kWp	7.8kWp
Max. PV input voltage	1000Vdc			
Rated input voltage	600Vdc			
Max. PV input current	13A/13A			
No. of MPPTs	2			
No. of PV strings per MPPT	1/1			
MPPT voltage range	200~950Vdc			
Starting voltage	200Vdc			
DC switch	Yes			
AC Output (On-grid)				
Rated AC output power	3kW	4kW	5kW	6kW
Max. output power	3.3kVA	4.4kVA	5.5kVA	6.6kVA
Rated AC output voltage	380/400/415Vac			
Rated output current	4.3A	5.8A	7.3A	8.7A
Max. output current	4.7A	6.4A	8.0A	9.6A
Rated grid frequency	50Hz/60Hz			
Grid frequency range	45~55Hz/55~65Hz			
Power factor	>0.99 (rated power)			
Adjustable power factor	0.8 (leading)~0.8 (lagging)			
THDi	<3% (rated power)			
Efficiency*				
Max. efficiency	98.50%			
European efficiency	98.00%			
MPPT efficiency	99.90%			
Function and protection				
Anti-islanding	Yes			
DC (PV) reversed connection	Yes			
AC short circuit protection	Yes			
Temperature protection	Yes			
Surge protection	DC Type II & AC Type III (Type II optional)			
AFCI function	Yes (optional)			
Zero-export function	Yes (optional)			
General				
Dimensions (W*H*D)	480*420*180mm			
Weight	18.5kg			
IP grade	IP65			
Self-consumption at night	<1W			
Cooling type	Natural cooling			
Altitude	4000m (>3000m derating)			
Operating temperature	-25°C~+60°C			
Relative humidity	0~100%			
Display	LCD+LED			
DC terminal	MC4 Terminal			
AC terminal	OT Terminal			
Installation method	Wall-mounted			
Communication	RS485, DRM (optional), WIFI (optional)/GPRS (optional)			
Compliance	EN 62109-1/2, IEC 62109-1/2, EN IEC 61000-6-1/3, IEC 62116, IEC 61727, EN 50549-1, NC RfG			

- *Data under laboratory test conditions.
- Specifications are subject to change without prior notice.

Kehua Digital Energy

Add: No. 457, Malong Road, Torch High-Tech Industrial Zone, Xiamen Fujian China

Tel: +86-592-5160516 Fax: +86-592-5162166 www.kehua.com

